

BATTERY POWERED MINI MILLER

Cut the Power Cord



The Mini Miller is now available as a cordless, battery powered model! It makes quick work of cleaning, descaling, and removing roots in pipes between DN50-100 (2-4") pipes and for cutting/reinstatements in DN50-75 (2-3") pipe. When paired with the Picote Mini Coating Pump it is capable of Picote Brush Coating™ in DN50-150 (2-6") pipes as well.

Now even easier to transport and operate regardless of power outlet locations or availability **(no need for a transformer in the UK).**

It's 8mm ($\frac{1}{8}$ ") shaft has a reach of 16m (50'), which can be extended 10m (32') by adding a shaft extension.

USES AND BENEFITS

- Use both hands on the shaft due to the operator presence foot control pedal.
- Operation times:
 - Up to 3 Hours w/Standard Battery (included)
 - Up to 4 Hours with High Output Battery*
- Conveniently charge battery even during use.
- Flexible: Navigate 90° bends.
- High Speed/High Torque: 550-2200 rpm (stepless speed control).
- Safety features include: protective outer shaft casing, electric safety clutch, operator presence foot control pedal, & E-stop.
- Reel brake standard.
- +C camera version or upgrade available.

*High Output Battery upgrade sold separately.

Technical Specifications

Technical Specifications	
Pipe Size Ranges	
Cleaning / Descaling	DN50-100 (2-4")
Cutting / Reinstatement	DN50-75 (2-3")
Picote Brush Coating™	DN50-150 (2-6")
Usable Shaft Length	16m (50')
Shaft Size	8mm ($\frac{1}{8}$ ")
Casing Type	Thick
Speed (RPM)	550-2200 (stepless speed control)
Power	UK/US: 110/120V, 15 Amp EU: 220/230V, 16 Amp
Weight	33kg (73 lbs) w/o battery
Battery Weight	Standard Output: 3.5kg (7.7 lbs) High Output: 4.1kg (9.0 lbs)
Size	740 x 519 x 404mm 29 x 20 x 16"
Safety Features	Protective outer shaft casing, operator presence foot control, electric clutch, & E-stop.

More Info/Guides/Technical Support:

- Visit picoteinstitute.com for e-learning courses, educational videos, quick guides, & manuals.
- For more information on products, spare parts, assembly and operation, consult the Safety & Operations Manual or contact Picote Technical Support.
- For hands-on product training, Picote operates training centers in USA, UK, and Finland.

PRODUCTS AND SPARE PARTS

Picote Battery Powered Mini Miller Products & Parts	
PN	Description
3540002817	Battery Powered Mini Miller EU
3540002817UK	Battery Powered Mini Miller UK
3540002817US	Battery Powered Mini Miller US
Spare Parts	
9540004011	Standard Battery
9540004035	High Output Battery
9540004013EU	Spare Charger for EU
9540004013UK	Spare Charger for UK
9540004013US	Spare Charger for US
131203108517	Mini Cleaner Replacement Shaft with Flexible Casing 16.4m (54')
9311713099	Mini Cleaner Shaft Spring Casing only 16.5m (54')
1350000020	Picote Flexible Shaft Lubricant bottle (0.5 litres/17oz)
1350000021	Picote Flexible Shaft Lubricant package (6 bottles)

