


LATERAL OPENING QUICK GUIDE

Version: 5 Issue Date: April 2024


MAXI MILLER

CAST IRON PIPES




Express Drill Chain





Smart Cutter[™]

STANDAR



UNLINED






Twister (unlined pipes)

Smart Cutter[™]




Twister (lined pipes)



Twister Express (unlined pipes)

Twister Express (lined pipes)



Tiger Twister (unlined pipes)


(lined pipes)



LINED

Refer to the Mini Cleaner / Mini Miller Range of Machines

FLOOR DRAIN



SIZE CHANGE



Special Drill Head

Special Drill

Head (3D)



Tiger Bore



Maxi Miller Shaft Diameter: 12mm (1/2") Range: 30 metres (100 ft) Shaft Extension*: Up to 15 metres (50 ft) Recommended Diameter Range: DN70-250 (3-10")

Available Tools Size Range

R D

S P E C I A

L

Twister	DN100-200 (4-8")
Twister Express	DN70-100 (3-4")
Tiger Twister	DN100-200 (4-8")
Express Drill Chain	DN100-150 (4-6")
Smart Cutter [™]	DN70-250 (3-10")
Special Drill Head	DN70-100 (3-4")
Special Drill Head (3D)	DN70-100 (3-4")
Tiger Bore	DN70-100 (3-4")
* Shaft extensions sold separately	

Please refer to your user operating manual before undertaking any work. Ask your reseller or contact Picote for further information. www.picoteinstitute.com